

TD-40 DRESSTA®



BASIC SPECIFICATIONS

Engine Range 515 hp - 528 hp
Weight 149,253 lb
Blade Capacity Range 24.3 - 52.1 yd³

KEY SPECIFICATIONS

Driveline

Engine Manufacturer / Model / Tier	Perkins/C 18/T4F
Displacement	1,098.4 in ³
Rated Speed	2000 RPM
Engine Output - Net	528 hp
Rated Speed - Torque	1500 RPM
Engine Torque	1,754.7 lb/ft
Transmission Type - Fwd Rev Speeds	Powershift - 6/6
Carrier Rollers / Track Rollers	2/6
Shoe Pitch	11.0 in
Track Shoe Width	24.0 in
Ground Contact Area	6,820.0 in ²
Number of Shoes	39

Capacities

Fuel Tank	359.8 Gal(US)
Hydraulic Tank	44.6 Gal(US)
Blade Capacity	24.3 yd ³

Dimensions

Height Top of ROPS (Max)	166.1 in
Width - Over Tracks	122.4 in
Track Length - On Ground	142.1 in
Blade Width	189.4 in

Performance

Speed Forward - Maximum	7.5 MPH
Speed Reverse - Maximum	9.3 MPH
Ground Bearing Pressure	21.9 psi
Drawbar Pull Maximum	261.2 lbf
Implement Pump Flow	14.1 cfm

Operating Weight

Operating Weight	149,252.8 lb
------------------	--------------